

## 2015 RIVAL SPEC SHEET

**A/A:** 35.30" +/- 0.10"

**B.H.:** 6.13" +/- 0.10"

**D.L.:** +3/8"

**String:** 28.152"

**Cable:** 41.437"

**Yoke:** 33.790"

CAMS:	DRAW LENGTH <sup>1</sup> :
PCXL#1	30"
PCXL#2	29.5"
PCXL#3	29"
PCXL#4	28.5"
PCXL#5	28"
PCXL#6	27.5"
PCXL#7	27"
PCXL#8	26.5"
PCXL#9	26"

Limb Deflections:	Draw Weights:
157	42-30
132	52-50
111	62-60
95	72-70

**Cam System:** PARALLEL Cam System-(PCXL)  
**Let-Off:** 85%  
**Spacers:** .080" on both sides<sup>3</sup>  
**Cable Guard:** FLEXIS-4 1/2" Length  
**Suppressor Rod:** P/N: W-000130 (Prime 2-Shot S.S Assembly -Short)  
**Bearings:** P/N: 12216  
**Pivots:** P/N: R-000027(Blue)  
**Timing:** Hole fully under limb +/-0.5 Hole

Notes:

- 1.) Minus nothing, plus 1/2"
- 2.) Measured with 5 grains/pound @ 70#.
- 3.) Spacer width +/- .005" to be within .005" from side to side.