

## 2014 PRIME ALLOY SPEC SHEET

**A/A:** 33.30" +/- 0.10"

**B.H.:** 6.7" +/- 0.10"

**D.L.:** +3/8"

**String:** 26"

**Cable:** 39.4"

**Yoke:** 33.75"

CAMS:	DRAW LENGTH <sup>1</sup> :
PCX#1	30"
PCX#2	29.5"
PCX#3	29"
PCX#4	28.5"
PCX#5	28"
PCX#6	27.5"
PCX#7	27"
PCX#8	26.5"
PCX#9	26"

Limb Deflections:	Draw Weights:
132	52-50
111	62-60
95	72-70

**Cam System:** PARALLEL Cam System-(PCX)  
**Let-Off:** 75%  
**Spacers:** .080" on both sides<sup>3</sup>  
**Suppressor Rod:** P/N: R-000130 (rod) & R-000005 (bumper)  
**Bearings:** P/N: 12216  
**Pivots:** P/N: R-000027(Blue)  
**Timing:** Hole half under limb +/-0.5 Hole

Notes:

- 1.) Minus nothing, plus 1/4"
- 2.) Measured with 5 grains/pound @ 70#.
- 3.) Spacer width +/- .005" to be within .005" from side to side.

