

2011 CENTROID/ 2012 CENTROID LR

SPEC SHEET

by NEG as of 10/26/11

A/A: 34.25” +/- 0.10”

B.H.: 7” +/- 0.10”

String: 26.350”

Cable: 38.900”

Yoke: 34.000”

CAM#1:	DRAW LENGTH ¹ :
PC#1	31”
PC#2	30.5”
PC#3	30”
PC#4	29.5”
PC#5	29”
PC#6	28.5”
PC#7	28”
PC#8	27.5”
PC#9	27”

Limb Deflections:	Limb Weights:	Limb Lengths:
92-89	51-54	13”-C1 Limbs
105-103	61-64	13”-C1 Limbs
126-124	71-74	13”-C1 Limbs

Cam System: PARALLEL Cam System-(PC)
Let-Off: 80%
Spacers: .065” on both sides³
Ti-Glide: P/N: 14502
Suppressor Rod: P/N :14496 set @ 1/16” from string
Bearings: Flanged - P/N:12216
Pivots: “+” Pivots (Black)
Timing: Tangent to Limb +/- .125”

Notes:

- 1.) Minus nothing, plus ¼”
- 2.) Measured with 5 grains/pound @ 70#.
- 3.) Spacer width +/- .005” to be within .005” from side to side.