

Prime One MX/STX 39 Specification Sheet

Technical Specifications

Axle to Axle;	39" (+/- 1/8")	Flex Guard Spring Length;	5"
Timing;	3rd mark tangent	Cam Spacers;	.080" (+/- .005" to fit)
Brace Height;	6.9-7.2"	String Stop Assembly;	W-000508
Letoff;	68-74%		

Cam System

PCS Cam (draw lengths are minus nothing, plus 1/4")

MOD NUMBER	A CAM	B CAM	C CAM
#1 Mod	31"	30"	28.5"
#2 Mod	30.5"	29.5"	28"
#3 Mod	30"	29"	27.5"
#4 Mod	29.5"	28.5"	27"
#5 Mod	29"	28"	26.5"
#6 Mod	28.5"	27.5"	26"
#7 Mod	28"	27"	25.5"
#8 Mod	27.5"	26.5"	25"
#9 Mod	27"	26"	24.5"
Limb Rockers	Red	Green	Blue

*Measured with B Cam. +6 fps for A Cam, -12 fps for C Cam

String Specifications

Serving Locations							Overall Length
String	1 1/2"	14"	17 1/2"	20 11/16"	22 11/16"	30 1/2"	32.03"
Cable	7"	16 1/16"	27 5/16"	33 3/4"	-	-	45.75"
A Yoke	14 1/4"	15 3/8"	16 7/8"	18"	-	-	32.3"
B Yoke	13"	14 1/4"	15 7/8"	17 1/16"	-	-	30.1"
C Yoke	11 3/8"	12 5/8"	14 3/16"	15 7/16"	-	-	26.82"