

2013 PRIME DEFY BOW SPEC SHEET

A/A: 31.30" +/- 0.10"

B.H.: 7.2" +/- 0.10"

D.L.: +3/8"

String: 24.060"

Cable: 37.530"

Yoke: 33.790"

CAMS:	DRAW LENGTH ¹ :
PCX#1	30"
PCX#2	29.5"
PCX#3	29"
PCX#4	28.5"
PCX#5	28"
PCX#6	27.5"
PCX#7	27"
PCX#8	26.5"
PCX#9	26"

Limb Deflections:	Draw Weights:
132	52-50
111	62-60
95	72-70

Cam System: PARALLEL Cam System-(PCX)
Let-Off: 75%
Spacers: .080/.085" on both sides³
Suppressor Rod: P/N: W-000129 (Prime 2-Shot S.S. Assembly-Long)
Ti-Glide: P/N: W-000131 (Prime 7" Cable Glide Assembly-Grey)
Bearings: P/N: 12216
Pivots: P/N: R-000027(Blue)
Timing: Hole half under limb +/-0.5 Hole

Notes:

- 1.) Minus nothing, plus ¼"
- 2.) Measured with 5 grains/pound @ 70#.
- 3.) Spacer width +/- .005" to be within .005" from side to side.



QF-697 Defy Bow Specification Sheet
 Rev. 1

Approved By: Scott Prater Date: 12/18/13