



SPECIFICATION SHEET

(Updated – 10/31/19)

Technical Specifications

Axle to Axle;	33" +/- .125"	Flex Guard Spring;	4" (2 dimples)
Timing;	Timing Dots Even	Cam Spacers;	.265"
Brace Height;	6 1/2" +/- .125"	String Stop Length;	6 5/8"
Centershot;	.672-.828"	Cam lean;	.150" Max

Draw Lengths

MOD POS.	DRAW LENGTH	ATA RATING*
1	31"	334-331
2	30 1/2"	331-328
3	30"	326-323
4	29 1/2"	324-320
5	29"	318-315
6	28 1/2"	314-311
7	28"	308-305
8	27 1/2"	304-300
9	27"	297-294
10	26 1/2"	292-289
11	26"	286-283
12	25 1/2"	280-277

*Estimated performance at 70lbs, 350 grains.

String Specifications

Serving Locations								Overall Length
String	2 1/2"	8 15/16"	12 15/16"	16 3/16"	18 3/16"	20 5/8"	-	25 7/8"
Cable	11"	15"	26 1/2"	-	-	-	-	31 1/8"
Upper Yoke	16 1/4"	17 1/16"	18 9/16"	19 3/8"	-	-	-	35 5/8"
Lower Yoke	14 3/4"	15 11/16"	17 3/16"	18 1/8"	-	-	-	32 7/8"
Cable Yoke	3 3/4"	6 3/8"	10 5/8"	13 1/4"	-	-	-	17"

Limb Deflections

Nominal Defl.	Defl. Range	Draw Weight*
56	53-59	80 lbs
62	59-65	70 lbs
67	64-70	65 lbs
72	69-75	60 lbs
84	81-87	50 lbs
102	99-105	40 lbs

*All draw weights are -0/+3 lbs.