



SPECIFICATION SHEET

(Updated – 11/12/19)

Technical Specifications

Axle to Axle;	39" +/- .125"	Flex Guard Spring;	4" (2 dimples)
Timing;	Timing Dots Even	Cam Spacers;	.265"
Brace Height;	7" +/- .125"	String Stop Length;	7 1/8"
Centershot;	.722"-.869"	Cam lean;	.150" Max

Draw Lengths

MOD POS.	DRAW LENGTH	ATA RATING*
1	33"	343-340
2	32 1/2"	340-337
3	32"	337-334
4	31 1/2"	334-331
5	31"	331-328
6	30 1/2"	328-325
7	30"	323-320
8	29 1/2"	324-317
9	29"	315-312
10	28 1/2"	311-308
11	28"	305-302
12	27 1/2"	301-297

*Estimated performance at 70lbs, 350 grains.

String Specifications

Serving Locations								Overall Length
String	2 1/2"	11 15/16"	15 15/16"	19 3/16"	21 3/16"	26 5/8"	-	31 7/8"
Cable	11"	20"	31 1/2"	-	-	-	-	37 1/8"
Upper Yoke	16 1/4"	17 1/16"	18 9/16"	19 3/8"	-	-	-	35 5/8"
Lower Yoke	14 3/4"	15 11/16"	17 3/16"	18 1/8"	-	-	-	32 7/8"
Cable Yoke	3 3/4"	6 3/8"	10 5/8"	13 1/4"	-	-	-	17"

Limb Deflections

Nominal Defl.	Defl. Range	Draw Weight*
56	53-59	80 lbs
62	59-65	70 lbs
67	64-70	65 lbs
72	69-75	60 lbs
84	81-87	50 lbs
102	99-105	40 lbs

*All draw weights are -0/+3 lbs.