

# Prime Nexus 2 Specification Sheet

## Technical Specifications

Axle to Axle;	32" +/- .125"	Flex Guard Spring;	Flexis Lite 3.5"
Timing;	Timing Dots Even	Cam Spacers;	.265"
Brace Height;	6" +/- .0625"	String Stop Length;	6 1/8"
Centershot;	.700" +/- .0625	Cam lean;	.150" Max

## Draw Lengths

MOD POS.	DRAW LENGTH
1	30"
2	29 1/2"
3	29"
4	28 1/2"
5	28"
6	27 1/2"
7	27"
8	26 1/2"
9	26"
10	25 1/2"
11	25"
12	24 1/2"
13	24
14	23 1/2"
15	23"

## String Specifications

Serving Locations								Overall Length
String	2 1/2"	8 7/16"	12 7/16"	15 11/16"	17 11/16"	19 5/8"	-	24 7/8"
Cable	11"	14 1/2"	26"	-	-	-	-	29 15/16"
Upper Yoke	16 1/4"	17 1/16"	18 9/16"	19 3/8"	-	-	-	35 5/8"
Lower Yoke	14 3/4"	15 11/16"	17 3/16"	18 1/8"	-	-	-	32 7/8"
Cable Yoke	3 3/4"	6 3/8"	10 5/8"	13 1/4"	-	-	-	17"

## Limb Deflections

Nominal Defl.	Defl. Range	Draw Weight*
56	53-59	80-83 lbs
62	59-65	70-73 lbs
67	64-70	65-68 lbs
72	69-75	60-63 lbs
84	81-87	50-53 lbs
102	99-105	40-43 lbs