

Prime Nexus 6 Specification Sheet

Technical Specifications

Axle to Axle;	36" +/- .125"	Flex Guard Spring;	Flexis Lite 3.825"
Timing;	Timing Dots Even	Cam Spacers;	.265"
Brace Height;	6 1/2" +/- .0625"	String Stop Length;	6 5/8"
Centershot;	.700" +/- .0625	Cam lean;	.150" Max

Draw Lengths

MOD POS.	DRAW LENGTH
1	31 1/2"
2	31"
3	30 1/2"
4	30"
5	29 1/2"
6	29"
7	28 1/2"
8	28"
9	27 1/2"
10	27"
11	26 1/2"
12	26"
13	25 1/2"
14	25"
15	24 1/2"

String Specifications

Serving Locations								Overall Length
String	2 1/2"	10 7/16"	14 7/16"	17 11/16"	19 11/16"	23 5/8"	-	28 7/8"
Cable	11"	16 1/2"	28"	-	-	-	-	33 15/16"
Upper Yoke	16 1/4"	17 1/16"	18 9/16"	19 3/8"	-	-	-	35 5/8"
Lower Yoke	14 3/4"	15 11/16"	17 3/16"	18 1/8"	-	-	-	32 7/8"
Cable Yoke	3 3/4"	6 3/8"	10 5/8"	13 1/4"	-	-	-	17"

Limb Deflections

Nominal Defl.	Defl. Range	Draw Weight*
56	53-59	80-83 lbs
62	59-65	70-73 lbs
67	64-70	65-68 lbs
72	69-75	60-63 lbs
84	81-87	50-53 lbs
102	99-105	40-43 lbs