

# Prime Inline 3 Specification Sheet

## Technical Specifications

<b>Axle to Axle;</b>	33" +/- .125"	<b>Flex Guard Spring;</b>	Flexis Lite 3.825"
<b>Timing;</b>	Timing Dots Even	<b>Cam Spacers;</b>	.265"
<b>Brace Height;</b>	6 1/2" +/- .0625"	<b>String Stop Length;</b>	6 5/8"
		<b>Cam lean;</b>	.150" Max

## Draw Lengths, Speeds (Estimated at 70-73lbs, 350 grains)

MOD POS.	DRAW LENGTH	ATA RATING
1	30 1/2"	328-333
2	30"	324-329
3	29 1/2"	319-324
4	29"	314-319
5	28 1/2"	309-314
6	28"	304-309
7	27 1/2"	298-303
8	27"	292-297
9	26 1/2"	286-291
10	26"	280-285

## String Specifications

Serving Locations	Overall Length
<b>String</b> 17 3/4" 26 5/16" 30 5/16" 33 9/16" 35 9/16" 41" - 59 1/4"	
<b>Cable</b> 12" 14 7/8" 27 5/16" 31 15/16" - - - 38.40"	

## Limb Deflections

Nominal Defl.	Defl. Range	Draw Weight*
56	53-59	80-83 lbs
62	59-65	70-73 lbs
67	64-70	65-68 lbs
72	69-75	60-63 lbs
84	81-87	50-53 lbs
102	99-105	40-43 lbs