

Prime Inline 5 Specification Sheet

Technical Specifications

| | | | |
|----------------------|------------------|----------------------------|----------------|
| Axle to Axle; | 35" +/- .125" | Flex Guard Spring; | Flexis Lite 3" |
| Timing; | Timing Dots Even | Cam Spacers; | .265" |
| Brace Height; | 6" +/- .0625" | String Stop Length; | 6 1/8" |
| | | Cam lean; | .150" Max |

Draw Length

| MOD POS. | MOD POS. | DRAW LENGTH |
|----------|----------|-------------|
| 1 | 1 | 30 1/2" |
| 2 | 2 | 30" |
| 3 | 3 | 29 1/2" |
| 4 | 4 | 29" |
| 5 | 5 | 28 1/2" |
| 6 | 6 | 28" |
| 7 | 7 | 27 1/2" |
| 8 | 8 | 27" |
| 9 | 9 | 26 1/2" |
| 10 | 10 | 26" |

String Specifications

| Serving Locations | | | | | | | | Overall Length |
|-------------------|---------|----------|----------|-----------|----------|-----|---|----------------|
| String | 17 3/4" | 27 5/16" | 31 5/16" | 34 9/16" | 36 9/16" | 42" | - | 61 1/4" |
| Cable | 12" | 15 7/8" | 28 5/16" | 32 15/16" | - | - | - | 40.40" |

Limb Deflections

| Nominal Defl. | Defl. Range | Draw Weight* |
|---------------|-------------|--------------|
| 56 | 53-59 | 80-83 lbs |
| 62 | 59-65 | 70-73 lbs |
| 67 | 64-70 | 65-68 lbs |
| 72 | 69-75 | 60-63 lbs |
| 84 | 81-87 | 50-53 lbs |
| 102 | 99-105 | 40-43 lbs |