

Prime Inline 3 Specification Sheet (updated 4/25/22)

Technical Specifications

Axle to Axle;	33" +/- .125"	Flex Guard Spring;	Flexis Lite 3.825"
Timing;	Timing Dots Even	Cam Spacers;	.265"
Brace Height;	6 1/2" +/- .0625"	String Stop Length;	6 5/8"
		Cam lean;	.150" Max

Draw Lengths, Speeds (Estimated at 70-73lbs, 350 grains)

MOD POS.	DRAW LENGTH	ATA RATING
1	30 1/2"	328-333
2	30"	324-329
3	29 1/2"	319-324
4	29"	314-319
5	28 1/2"	309-314
6	28"	304-309
7	27 1/2"	298-303
8	27"	292-297
9	26 1/2"	286-291
10	26"	280-285

String Specifications

Serving Locations								Overall Length
String	18"	26 3/8"	30 3/8"	33 5/8"	35 5/8"	39 7/16"	-	59.345"
Cable	12"	14 15/16"	27 3/8"	32 1/16"	-	-	-	38.525"

Limb Deflections

Nominal Defl.	Defl. Range	Draw Weight*
56	53-59	80-83 lbs
62	59-65	70-73 lbs
67	64-70	65-68 lbs
72	69-75	60-63 lbs
84	81-87	50-53 lbs
102	99-105	40-43 lbs