

Prime Inline 5 Specification Sheet (updated 4/25/22)

Technical Specifications

Axle to Axle;	35" +/- .125"	Flex Guard Spring;	Flexis Lite 3"
Timing;	Timing Dots Even	Cam Spacers;	.265"
Brace Height;	6" +/- .0625"	String Stop Length;	6 1/8"
		Cam lean;	.150" Max

Draw Lengths, Speeds (Estimated at 70-73lbs, 350 grains)

MOD POS.	DRAW LENGTH	ATA RATING
1	30 1/2"	333-338
2	30"	329-334
3	29 1/2"	324-329
4	29"	319-324
5	28 1/2"	314-319
6	28"	309-314
7	27 1/2"	303-308
8	27"	297-302
9	26 1/2"	291-296
10	26"	285-290

String Specifications

Serving Locations								Overall Length
String	18"	27 3/8"	31 3/8"	34 5/8"	36 5/8"	41 7/16"	-	61.345"
Cable	12"	15 15/16"	28 3/8"	34 1/16"	-	-	-	40.525"

Limb Deflections

Nominal Defl.	Defl. Range	Draw Weight*
56	53-59	80-83 lbs
62	59-65	70-73 lbs
67	64-70	65-68 lbs
72	69-75	60-63 lbs
84	81-87	50-53 lbs
102	99-105	40-43 lbs