

2015 RIVAL SPEC SHEET

A/A: 35.30" +/- 0.10"

Yoke: 33.790"

B.H.: 6.13" +/- 0.10"

D.L.: +3/8"

String: 28.152"

Cable: 41.437"

CAMS:	DRAW LENGTH ¹ :	IBO RATING ² :
PCXL#1	30"	336-331
PCXL#2	29.5"	331-326
PCXL#3	29"	326-321
PCXL#4	28.5"	321-316
PCXL#5	28"	316-311
PCXL#6	27.5"	311-301
PCXL#7	27"	301-296
PCXL#8	26.5"	296-291
PCXL#9	26"	291-286

Limb Deflections:	Draw Weights:
157	42-30
132	52-50
111	62-60
95	72-70

Cam System: PARALLEL Cam System-(PCXL)
Let-Off: 85%
Spacers: .080" on both sides³
Cable Guard: FLEXIS-4 1/2" Length
Suppressor Rod: P/N: W-000130 (Prime 2-Shot S.S Assembly -Short)
Bearings: P/N: 12216
Pivots: P/N: R-000027(Blue)
Timing: Hole fully under limb +/-0.5 Hole

Notes:

- 1.) Minus nothing, plus 1/2"

- 2.) Measured with 5 grains/pound @ 70#.
- 3.) Spacer width +/- .005" to be within .005" from side to side.

Rival Spec Sheet REV 1 110514